

ER-RRun20 med Cummin motor !

MODEL	STANDARD utrustning	PRIS
ER-RRun20	Standard Bucket, Hydraulic Torque Converter Transmission, Floating Function, Mechanical Joystick, 130W Heater, 220V Engine Heater, Rops&Fops Cabin, Tipping Cabin, Luxury Cabin Inside, Backward Imagine, Comfortable Seat, Adjustable Steering Wheel, Wheel Reducer Axle, Air Brake, Lock for Lifting and Steering Cylinder, Hydraulic Pressure Check System, Parallel Linkage, 16/70-20 Tire,	205900 SEK
PICTURE I		PICTURE II
		

OPTIONS

Mixer Bucket	16000 SEK	Hydraulic Snow Blade	14900 SEK
Quick Hitch	INGÅR	Sweeper	16900 SEK
Pallet Forks	3900 SEK	Snow Blower	UTGÅTT tillsvdare
European Grapple Forks	13500 SEK	Tyre Chain	5400 SEK
Grapple Bucket	14900 SEK	4 in 1 Bucket	11900 SEK
Wooden Forks	14900 SEK	Adjustable Pallet Forks	8900 SEK
Electric Joystick	INGÅR	Sand Spreader	16900 SEK
Hydraulic Line(per one more)	INGÅR	E4 Lamp	INGÅR
LED Light	INGÅR	Snow Bucket with Wings	15900 SEK

POLARPROD ab Hamngatan 1 38540 Bergkvara (Kalmar)
polarprod@gmail.com

Snow Bucket	7000 SEK	Bale Grab	6500 SEK
Varta Anti-freeze Battery	INGÅR		00
		Air Conditioner	6900 SEK
		Planerings skopa	INGÅR

SPECIFIKATIONER:

1.0 Engine Details	
(1) Model:	Cummins QST3.8 (EuroIII Standard)
(2) Engine Type:	In-line arrangement, water-cooled, four-cycle diesel engine
(3) Rated Power:	55 KW
(4) Rated Speed:	2400 r/min(rpm)
(4) Fuel Consumption ration in Standard Working Condition:260g/kw.H	
2.0 Transmission System	
(1) Type:	Fixed-spindle Power Shift
(2) Shift Gear Control Oil Pressure	1.0-1.8MPa
(3) Rated Input Speed:	2500(rpm)
3.0 Bucket	
(1) Bucket Capacity:	0.72 m3
(2) Bucket Width:	2040mm
(3) Bucket Type:	Heavy-duty Bolt on Teeth
(5) Rated Load:	2000kg
(6)Operating Weight	5200kg
4.0 Overall Dimensions	
(1) Overall Length(bucket on ground)	5710mm
(2) Overall Height	
(3) Ground to Cab Top:	2800mm
(4) Dumping Height:	2850mm
(5) Min. Base to the Ground	275mm
(6) Overall Width	2040mm
5.0 Operating Specifications	
(1) Steering System:	Articulated Frame with Hydraulic Power Steering
(2) Min. Turning Radius:	5460mm
(3) Driving System:	Hydraulic Converter
6.0 Brake System	
(1) Service Brake	Four Wheel Hydraulic Spread-shoed Brake
(2) Parking Brake	Hand Operated
7.0 Tyre	16/70-20

