

EVERRUN 1200 by Polarprod, Sweden

Modell	Standardutrustad	Pris
ER-RRun 12	Välj mellan Standard (jord/ grus) alt planerings skopa,, Hydraulisk konverter Transmission, Euro III Engine, Quick Hitch, Flytläge, 130W Värmare, 220V motorvärmare, Rops&Fops Hytt, Tippbar hytt, Backkamera, Justerbar stol, Justerbar ratt, reducerings axlar, Trumbromsar, Lås för lyft och styr-cylinder, Hydrauliskt tryck kontrol System, Parallel föring, Värmepaket på höger utsida med inspektionslucka ” Däck 20,5/70-16	119900SEK (tillsvidare, reservation för ev ändringar)



Tillval & Tillbehör

Pallgafflar	4900 SEK	Hydrauliskt snöblad	16900 SEK
20.5/70-16 "breda däck"	INGÅR i priset	Sopaggregat	15900 SEK
Mixer Bucket	11900 SEK	Snow Blower	Utgått tillsvidare
European Grapple Forks	12900 SEK	En valfri skopa Planering alt Standard skopa	INGÅR i priset
Grapple Bucket	12900 SEK	4 in 1 Bucket	11780 SEK
Wooden Forks	12470 SEK	Hydrauliska pallgafflar	9900 SEK
Electric växel på joystick	10000SEK	Sand Spridare	16440 SEK
3-4:de funktion	INGÅR i priset	E4 Lamp	2400 SEK
LED Light	2200 SEK	Snow Bucket hyd-Wings	16000 SEK

Specifikationer:

1.0 Engine Details	
(1) Model Motor:	C490BPG Engine(EuroIII Engine)
(2) Engine Type:	In-line Arrangement, Water-cooled, Four-cycle Diesel Engine
(3) Rated Power:	36.8 KW
(4) Rated Speed:	2650 r/min(rpm)
(4) Fuel Consumption Ration in Standard Working Condition: 252 g/kw.H	
2.0 Transmission System	
(1) Type:	Fixed-spindle Power Shift
(2) Shift Gear Control Oil Pressure	1.0-1.8MPa
(3) Rated Input Speed:	2500(rpm)
3.0 Bucket	
(1) Bucket Capacity:	0.53 m ³
(2) Bucket Width:	1740mm
(3) Bucket Type:	Heavy-duty Bolt on Teeth
(5) Rated Load:	1200kg
(6)Operating Weight	3400kg
4.0 Overall Dimensions	
(1) Overall Length(bucket on ground)	5200mm
(2) Overall Height	

7.0 Tyre

20.5/70-16

(2) Min. Turning Radius:

5200mm

(3) Driving System:

Hydraulic Converter

6.0 Brake System**(1) Service Brake**

Four Wheel Hydraulic Spread-shoed Brake

(2) Parking Brake

Hand Operated

(3) Ground to Cab Top:

2550mm

(4) Dumping Height:

2450mm

(5) Min. Base to the Ground

240mm

(6) Overall Width

1740mm

5.0 Operating Specifications**(1) Steering System:**

Articulated Frame with Hydraulic Power Steering



POLARPROD AB Hamngatan 1 83540 Bergkvara (Kalmar)

polarprod@gmail.com