

## ER-RRun 800 (zl 08)

| MODEL    | STANDARD Utrustning  | Pris   |
|----------|--|--|
| ERRUN800 | <p><b>Välj mellan Standard ( jord/ grus) alt planerings skopa</b><br/>                     Konverter, Flyt funktion på lastaren, Joystick mekanisk, 3&amp;4e funktion på lastaren, 130W Heater, 220V motor värmare , Rops &amp; Fops Hytt, Fällbarhytt, Backkamera, Hydrauliskt tryck kontroll System, Parallell föring på lastaren, Värmepaket på högerdörr utsida med inspektionslucka.<br/> <b>Däck 31*15.5-15, 35 mm</b></p> | <p><b>99 900 SEK<br/>+ moms</b></p> <p>(tillsvidare, reservation för ev ändringar)</p> |



### Tillval & Tillbehör

|  |           |                         |                |
|--|-----------|-------------------------|----------------|
| Mekaniska pallgafflar                        | 4900 SEK  | Hydrauliskt snöblad     | 14900 SEK      |
| Quick Hitch ( 3 & 4: E funktion )            | INGÅR     | Sop aggregat            | 15900 SEK      |
| Elektrisk växel på joystick                  | 10000 SEK | Snow Blower             | utgått         |
| European Grapple Forks                       |           | Snökedjor               | 3500 SEK / par |
| Grapple Bucket                               |           | 4 in 1 Bucket           |                |
| Wooden Forks                                 |           | Hydrauliska pallgafflar | 9900 SEK       |
| Auger  |           | Sand Spridare           | 16900 SEK      |
| 3 - 4:de funktion                            | ingår     | E4 Lamp                 | 2400 SEK       |
| LED Light                                    | 2200 SEK  | Snöskopa med klaffar    | 15900 SEK      |
| En valfri skopa Planering alt Standard skopa | INGÅR     | Varta vinter batteri    | 1000 SEK       |

## Specifikationer:

### 1.0 Engine Details

|  |  |
|--|--|
| (1) Model:   | ZN390Q   |
| (2) Engine Type:   | In-line Arrangement, Water-cooled, Three-cycle Diesel Engine |
| (3) Rated Power:   | 25 KW  |
| (4) Rated Speed:   | 2500 r/min(rpm)  |
| (4) Fuel Consumption Ration in Standard Working Condition: | 252 g/kw.H   |

### 2.0 Transmission System

|                                     |                           |
|-------------------------------------|---------------------------|
| (1) Type:                           | Fixed-spindle Power Shift |
| (2) Shift Gear Control Oil Pressure | 1.0-1.8MPa                |
| (3) Rated Input Speed:              | 2500(rpm)                 |

### 3.0 Bucket

|                      |                          |
|----------------------|--------------------------|
| (1) Bucket Capacity: | 0.48 m3                  |
| (2) Bucket Width:    | 1600mm                   |
| (3) Bucket Type:     | Heavy-duty Bolt on Teeth |
| (5) Rated Load:      | 800kg                    |
| (6) Operating Weight | 2700kg                   |

### 4.0 Overall Dimensions

|                                      |        |
|--------------------------------------|--------|
| (1) Overall Length(bucket on ground) | 4620mm |
| (2) Overall Height                   |        |
| (3) Ground to Cab Top:               | 2540mm |
| (4) Dumping Height:                  | 2120mm |
| (5) Min. Base to the Ground          | 220mm  |
| (6) Overall Width                    | 1500mm |

### 5.0 Operating Specifications

|                          |   |
|--------------------------|---|
| (1) Steering System:     | Articulated Frame with Hydraulic Power Steering |
| (2) Min. Turning Radius: | 5200mm  |
| (3) Driving System:      | Hydraulic Converter                             |

### 6.0 Brake System

|                   |   |
|-------------------|---|
| (1) Service Brake | Four Wheel Hydraulic Spread-shoed Brake |
| (2) Parking Brake | Hand Operated                           |

### 7.0 Tyre

31\*15.5-15

POLARPROD ab Hamngatan 1 38540 Bergkvara (kalmar) [polarprod@gmail.com](mailto:polarprod@gmail.com)