



Drive Type 4WD

Overall Dimensions L*W*H(mm): 2055*945*1050

Wheel Track (mm) Front 800, Rear 740,840,940

Wheel Bass(mm) 1280

Ground Clearance (mm) 250

Rated Traction Force(N) 3900

Construction Mass(kg) 552 Min.Turning Radius(m) 2.30

Theoretical Speed (km/h) Forward 1.32,1.95,3.04,6.01,8.9,13.92 Reverse 1.63,7.46

Engine Specifications Model 3M78 Type 3-Cylinder Vertical,water cooled,4 stroke cycle Rated Power(kw/hp) 11.8/16 Rated Speed (rpm) 2300 Bore*Stroke (mm) 75*77.6

Total Displacement(L) 1.028 DriveSystem Clutch 7'Single Stage Gear Box (3+1)*2 Main Drive Columniform gear Differential Bevel Gear Differential Lock Jaw Lock Final Transmission Spur Gear, External gearing Traveling Mechanism

Tyre Front 5.00-12 Rear 7.5-16 Steering Gear Power Steering, Brake: Disc type

Working Device Hydraulic System Lifting Capacity at 610mm Behind Lift Point (N) 2280

3-Point Suspension Category:0 P.T.O Shaft Rotating Speed (rpm) 540/720/1000

POLARPROD AB Tel: 0640 42002, Mail: polarprod@gmail.com

**59900:- inkl lastare
och skopa + moms**